

AMENDMENTS TO THE CLAIMS

1. (Previously Presented) A system for a magnetic head arm assembly (HAA) comprising:

a first component having a first cavity to be coupled to an arm portion having an arm cavity via insertion of a pin element, independent of the first component and the arm portion, through the first cavity and the arm cavity and welded between said first component and said arm portion, wherein the surface of said pin element is directly attached to and physically connected along a surface of said first component and a surface of said arm portion,

and wherein said first component is selected from the group consisting of a head suspension portion and a flex cable portion.

2. (Original) The system of claim 1, wherein said head suspension portion is a hard disk drive head gimbal assembly (HGA).

3. (Original) The system of claim 1, wherein said flex cable portion is a hard disk drive flex cable.

4. (Original) The system of claim 1, wherein said arm portion is a hard disk drive arm.

5. (Original) The system of claim 1, wherein said pin element is a copper welding pin.

6. (Cancelled).
7. (Original) The system of claim 5, wherein said pin element is cylindrical; said first cavity is a circular hole with a diameter enabling insertion of said pin element; and said arm cavity is a circular recession with a diameter enabling insertion of said pin element.
8. (Original) The system of claim 5, wherein said pin element has a rectangular cross-section; said first cavity is a rectangular opening with a size enabling insertion of said pin element; and said arm cavity is a rectangular recession with a size enabling insertion of said pin element.
9. (Original) The system of claim 5, wherein said pin element is interference fitted into said arm cavity and said pin element is soldered to first component to couple said first component to said arm portion.
10. (Previously Presented) A method for a magnetic head arm assembly (HAA) comprising:
coupling a first component having a first cavity to an arm portion having an arm cavity via insertion of a pin element, independent of the first component and the arm portion, through the first cavity and the arm cavity and welded between said first component and said arm portion, wherein the surface of said pin element is directly attached to and physically connected along a surface of said first component and a surface of said arm portion,

and wherein said first component is selected from the group consisting of a head suspension portion and a flex cable portion.

11. (Original) The method of claim 10, wherein said head suspension portion is a hard disk drive head gimbal assembly (HGA).

12. (Original) The method of claim 10, wherein said flex cable portion is a hard disk drive flex cable.

13. (Original) The method of claim 10, wherein said arm portion is a hard disk drive arm.

14. (Original) The method of claim 10, wherein said pin element is a copper welding pin.

15. (Cancelled).

16. (Original) The method of claim 14, wherein said pin element is cylindrical; said first cavity is a circular hole with a diameter enabling insertion of said pin element; and said arm cavity is a circular recession with a diameter enabling insertion of said pin element.

17. (Original) The method of claim 14, wherein said pin element has a rectangular cross-section; said first cavity is a rectangular opening with a size enabling insertion of said pin

element; and said arm cavity is a rectangular recession with a size enabling insertion of said pin element.

18. (Original) The method of claim 14, wherein said pin element is interference fitted into said arm cavity and said pin element is soldered to first component to couple said first component to said arm portion.

19. (Previously Presented) A system for a magnetic head arm assembly (HAA) comprising:
a first component having a first cavity to be coupled to a second component having an arm cavity via a pin independent of the first component and the second component and welding said first component to said second component, wherein

said first component is selected from the group consisting of a head suspension portion, a flex cable portion, and a flex circuit portion; and

said second component is an arm portion

and wherein the surface of said pin element is directly attached to and physically connected along a surface of said first component and a surface of said arm portion.

20. (Original) The system of claim 19, wherein said first component is a hard disk drive slider frame and said second component is selected from a group consisting of a hard disk drive head gimbal assembly (HGA) and a hard disk drive slider.

21. (Original) The system of claim 19, wherein said head suspension portion is a hard disk drive head gimbal assembly (HGA).

22. (Original) The system of claim 19, wherein said flex cable portion is a hard disk drive flex cable.

23. (Original) The system of claim 19, wherein said flex circuit portion is a hard disk drive bridge flex circuit (BFC).

24. (Original) The system of claim 19, wherein said arm portion is a hard disk drive arm.

25. (Original) The system of claim 19, wherein said first component is coupled to said second component via a type of welding selected for the group consisting of ultrasonic welding, solder bump welding, and laser welding.

26. (Original) The system of claim 20, wherein said first component is coupled to said second component via a type of welding selected for the group consisting of ultrasonic welding, solder bump welding, and laser welding.

27. (Previously Presented) A method for a magnetic head arm assembly (HAA) comprising:
welding a first component having a first cavity to a second component having an arm cavity, wherein the first component and the second component are coupled via a pin independent

of the first component and the second component; and wherein

said first component is selected from the group consisting of a head suspension portion, a flex cable portion, and a flex circuit portion; and

said second component is an arm portion and wherein the surface of said pin element is directly attached to and physically connected along a surface of said first component and a surface of said arm portion.

28. (Original) The method of claim 27, wherein said first component is a hard disk drive slider frame and said second component is selected from a group consisting of a hard disk drive head gimbal assembly (HGA) and a hard disk drive slider.

29. (Original) The method of claim 27, wherein said head suspension portion is a hard disk drive head gimbal assembly (HGA).

30. (Original) The method of claim 27, wherein said flex cable portion is a hard disk drive flex cable, said flex circuit portion is a hard disk drive bridge flex circuit (BFC), and said arm portion is a hard disk drive arm.

31. (Original) The method of claim 27, wherein said first component is coupled to said second component via a type of welding selected for the group consisting of ultrasonic welding, solder bump welding, and laser welding.

Application No.: 10/634,269
Amendment dated: February 28, 2008
Reply to Office Action of November 28, 2007

32. (Original) The method of claim 28, wherein said first component is coupled to said second component via a type of welding selected for the group consisting of ultrasonic welding, solder bump welding, and laser welding.